



Commercial status

End of Commercialisation : MAR 27, 2020

⚠ End of Commercialisation

Main

Device short name	AS-P
Product certifications	BTL FCC part 15 class B ICES-003 CULus CE
Width	90 Mm
Product or component type	Controller
Communication service	SNMP network management SMTP e-mail notification SMTPS e-mail notification Modbus TCP client Modbus TCP server
Net weight	321 G
Depth	64 Mm
Ambient air temperature for operation	0...50 °C
IP degree of protection	IP20
Flame retardance	UL94V0-5VB
Current consumption	400 mA
Height	114 Mm
Ambient air temperature for storage	-20...70 °C
Standards	UL 94 UL 916 FCC CFR 47 part 15
Memory type	512 MB RAM 4 GB flash
Product brand	Schneider Electric
Range	EcoStruxure Building Operation

Complementary

Product mounting	On base DIN rail
I/O limit processor capacity	464 I/O, 29 modules
Material	ABS/PC
Web services	Programmable scripts : alarm summaries, report management HTTP server TLS 1.0
Range compatibility	TB-ASP-W1 terminal base TB-AS-W1 terminal base
Processor name	Spear 320s
Communication port protocol	BACnet Modbus TCP master RS485 Modbus TCP slave RS485 HTTPS RJ45 HTTP RJ45 LON TP/FT-10
Integrated connection type	USB 2.0 type A USB type mini B

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	229.0 G
Package 1 Height	5.8 Cm
Package 1 width	9.0 Cm
Package 1 Length	11.8 Cm
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Weight	4.559 Kg
Package 2 Height	15.0 Cm

Package 2 width	30.0 Cm
Package 2 Length	40.0 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product Life Status :	End of commerc. - Block
-----------------------	--------------------------------