

Product data sheet

Specifications



modular safety transformer - 230 V
50..60 Hz - output 12..24 V - 25 VA

15219

! Discontinued on: 01 April 2019

! Discontinued

Main

Transformer type	Safety transformer
Range of product	TR
Product or component type	Transformer
Device short name	TR

Complementary

[Ue] rated operational voltage	230 V AC 50/60 Hz
Output voltage	12/24 V: +/-5 % on load 14/28 V: off load
Output short-circuit protection	Built-in
Rated power in VA	25 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	10
Height	89 mm
Width	90 mm
Depth	60 mm
Auxiliary connection terminal	Tunnel type terminals 4 mm ²

Environment

Standards	EN 61558-2-6 EN 60742 IEC 61558-2-6
Product certifications	NF
Overvoltage category	Class II with terminal shields in option
Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-25...80 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Package 1 Weight 1.125 kg

Package 1 Height 0.650 dm

Package 1 width 0.900 dm

Package 1 Length 0.900 dm

Contractual warranty

Warranty 18 months

Recommended replacement(s)

15219 is replaced by:

1x



modular safety transformer iTR - 230 V 50..60 Hz - output 12..24 V - 25 VA
A9A15219
